

# HS-JP-1/2-6FT-XX-XX

XX type 1/2" Feeder Jumper Cable

DC~6GHz

| Part No.             | HS-JP-1/2-6FT-4310M-NM  | HS-JP-1/2-6FT-DINM-NM | HS-JP-1/2-6FT-NM-NM | HS-JP-1/2-6FT-NF-NM |
|----------------------|---|-----------------------|---------------------|---------------------|
| <b>Electricals</b>   |   |                       |                     |                     |
| Frequency range      | DC~6GHz   |                       |                     |                     |
| VSWR                 | $\leq 1.2 @ 600\sim 2700\text{MHz}$ , $\leq 1.25 @ 2700\sim 6000\text{MHz}$ , |                       |                     |                     |
| PIMD                 | $\leq -155\text{dBc}@2\times 43\text{dBm}(698\sim 2700\text{MHz})$            |                       |                     |                     |
| Impedance            | 50 $\Omega$   |                       |                     |                     |
| <b>Environmental</b> |   |                       |                     |                     |
| Operating temp.      | -30°C ~ 80°C  |                       |                     |                     |
| Relative humidity    | 5% ~ 95%  |                       |                     |                     |
| Application          | Indoor or Outdoor(IP68)   |                       |                     |                     |
| <b>Mechanicals</b>   |   |                       |                     |                     |
| Cable Type & Length  | 1/2" Flexible / 6ft   |                       |                     |                     |
| Connector A          | 4.3-10 Male   | DIN-type Male         | N type Male         | N type Female       |
| Connector B          | N type Male   | N type Male           | N type Male         | N type Male         |

